
# **Beta 43 (BV1903)**

## 4 Cylinders - 1857cc - 43bhp max at 2,800 rev/min - 243Kg





Fuel Consumption based on theoretical propeller loading - matched at full speed

#### Standard Control Panel - ABV

## **Standard Specification**

**Beta Marine - Beta 43** - 4 cylinder, naturally aspirated, diesel propulsion engine developing 43 bhp at 2,800 rpm with a swept volume of 1,857 cc (Recreational Craft Directive emission compliant). The engine is supplied complete with a heat exchanger and header tank, water cooled exhaust manifold, fresh and sea water pumps, cast injection bend, mechanical fuel lift pump, fuel and oil filters, sump pump, flywheel with heavy inertia ring for super smooth running at low rpm, flywheel housing, special quiet air intake filter, 12 volt starter, 65 amp battery charging alternator, shutdown solenoid, control panel "ABV" (with tachometer/hour recorder, keystart switch and push button stop, warning lights and alarm buzzer for low oil pressure, high water temperature, no charge, and power on); a 3m interconnection cable with multi pin plug and socket to engine harness. Gearbox with nominal 2:1 reduction, heavy duty engine feet with flexible mountings, "Morse" type end fittings for speed and gear control, engine test certificate, operators manual. Red paint and packed on skid base with a 3 year "Self Service" warranty.



### **Standard Features**

- Reliable heat exchanger cooled, naturally aspirated, indirect injection diesel engine, based upon Kubota's highly advanced technology.
- Cast iron cylinder head and block with a gear driven camshaft and sea water pump.
- Three vortex combustion system for quiet running, excellent fuel consumption, and emission compliance in all countries.
- Installation angles up to 15° maximum when static, and 25° when heeling.
- Technodrive or PRM gearboxes. Output rotation is clockwise in ahead viewed from gearbox end.

### **Optional Extras**

- Special engine feet to suit your installation requirements.
- Shallow sump.
- 12 Volt 100 Amp alternator; and second alternator available.
- Keel cooling.
- Control Panels ABVW, B or C with gauges and alarms.
- See price list for a comprehensive range of accessories to cover a complete engine installation.

## Detailed engine drawings, brochures and manuals are available to download



Beta Marine Limited, Davy Way, Waterwells, Quedgeley, Gloucester GL2 2AD, U.K. Tel: +44 (0)1452 723492 Fax: +44 (0)1452 883742 sales@betamarine.co.uk