
BETA MARINE

SAILDRIVES 13.5, 20 & 28 hp



STANDARD SPECIFICATION

- Heat exchanger cooled diesel engine with header tank, indirect injection, naturally aspirated, based on Kubota.
- Smooth running with multi-cylinder and high inertia flywheel.
- Water cooled exhaust manifold.
- Fresh and sea water pumps
- Three vortex combustion for quiet running, low emissions and excellent fuel consumption.
- 12 volt electric starting with 40 amp battery charging alternator.
- Heater plugs for cold start below 5°C.
- Control Panel type "ABV" as standard with 3 metre interconnection cable and multi pin plug and socket.
- GRP base for "glassing" into the hull and flexible engine mountings.
- Engine with heat exchanger and header tank



- Fuel filter and mechanical fuel lift pump.
- · Lubricating oil filter and sump drain pump.
- Saildrive 2.2: I reduction
- Morse type cable support and end fittings for engine speed and gearbox control.
- Engine test certificate and operator's manual.

OPTIONS


- Deluxe "C" Control panel
- 65 amp alternator (in lieu of 40 amp).
- 2 blade folding propeller.





Standard "ABV" panel



Optional "C" panel







BETA MARINE

Merretts Mills, Bath Road, South Woodchester, Stroud, Glos. GL5 5EU. U.K. Tel: +44 (0) 1453 835282. Fax: +44 (0) 1453 835284 www.betamarine.co.uk Email: sales@betamarine.co.uk